

Introducing the TDTG102 Tire Pressure Gauge



SPECIFICATIONS

- PSI Range: 2.0 to 100.0 PSI
- Bar Range: 0.15 to 7.0 BAR
- KPA Range: 15 to 700 KPA
- Display: ¼" LCD
- Power: battery
- Temperature Range: 32°-104°F
- Illuminated Tip & Backlight Display
- Rubberized Grip
- Rugged Design
- One Button Operation

INSTRUCTIONS

- Press the ON button. Wait for 0.0 PSI, 0.00 BAR, or 0 KPA display.
- The unit can be changed from PSI to BAR to KPA by pressing the ON button after the gauge is turned on.
- Make sure there is a good seal between the nozzle and the valve by pressing firmly.
- There should be no hissing sound or air leakage when pressing the nozzle onto the valve.
- Wait 3 seconds. Remove the nozzle from the valve. An accurate reading of the tire pressure will be displayed.
- Wait 3 seconds before taking another reading.
- The gauge will automatically turn off after 90 seconds from the last reading.
- The gauge can also be turned off by pressing and holding the ON button for 3-5 seconds.

®

HELPFUL HINTS

- Always be sure to follow the tire manufacturer's recommended pressure ratings.
- The electronic module and power cells (batteries) are factory sealed in the unit. There are no user parts or adjustments to be made.
- To clean the gauge, use a soft damp cloth, DO NOT immerse in or spray with water, other liquids or abrasive cleaners.